



Application method

Rubber streak removal

Tyre marks from forklift trucks can cause heavy soiling on flooring. Rubber streak removal can remove these kinds of dirt from solvent-resistant floor coverings.



Step 1: Remove coarse dirt

Sweep or damp wipe to remove coarse, loose dirt.



Step 2: Dose, prepare ready-to-use solution

First add water, then add the correct amount of detergent, following the dosage instructions on the label. Always use cold water!

Follow operating instructions. Wear personal protective equipment.



Step 3: Apply the cleaning solution to required areas

Pour the product solution into a suitable spray device with a foam nozzle. Apply foam to the soiled areas. Do not allow the cleaning solution to dry.



The safety advice and instructions for use on the containers, the product information and the safety data sheet must be observed. Please also observe the cleaning and maintenance recommendations of the manufacturers as well as the instruction manual of the machines and equipment used.



Application method

Rubber streak removal



Step 4: Mechanical wet cleaning

Fill cleaning machine with 1% Dopomat-forte solution. Cover the area in even, overlapping strokes to remove the pre-treated dirt.



Step 5: Large-scale application

Cover an area of approx. 25 sq m with the product solution. Protect any adjacent surfaces that are sensitive to solvents. Do not allow the cleaning solution to dry.



Step 6: Scrubbing the surface

Scrub the area with a rotary floor machine and a suitable pad or with a cleaning machine. Scrub edges with a hand pad if required.



The safety advice and instructions for use on the containers, the product information and the safety data sheet must be observed. Please also observe the cleaning and maintenance recommendations of the manufacturers as well as the instruction manual of the machines and equipment used.



Application method

Rubber streak removal



Step 7: Vacuum up loose dirt

Vacuum up loosened dirt with a wet vacuum cleaner or cleaning machine.



Step 8: Remove residue

Use an alkaline industrial cleaner for cleaning the surfaces with a cleaning machine or rotary floor machine until all product residue has been removed.



Step 9: Clean the devices

Rinse the wet vacuum cleaner, rotary floor machine, bucket etc. and clean inside and out with a cloth. Clean the cable with a cloth and check for damage.

