



Application method

Spray buffing with Kiehl-Basic-Oil

Spray buffing can remove stubborn dirt, while worn oil surfaces can be improved by spraying with suitable care products. This will freshen up the colour of the surface.



Step 1: Preparation

Stack furniture where necessary. Sweep or use a damp cloth (gauze cloth) to remove coarse, loose dirt.



Step 2: Prepare machine and ready-to-use solution

Check machine for damage. Affix a suitable pad below the rotary floor machine. Pour Kiehl-Basic-Oil into a suitable spray bottle.



Step 3: Spray buffing

Spray the surface sparingly with the product solution in sections. Polish the damp surface with the machine and an appropriate pad until a shine appears or dirt has been removed. Turn over or replace pads regularly.

Tip!

When using high-speed machines, use a starting current limiter to prevent fuses from "blowing out".



The safety advice and instructions for use on the containers, the product information and the safety data sheet must be observed. Please also observe the cleaning and maintenance recommendations of the manufacturers as well as the instruction manual of the machines and equipment used.



Application method

Spray buffing with Kiehl-Basic-Oil



Warning:

Oxidation-drying oils can lead to spontaneous combustion in conjunction with wood dust, cloths, pads and other absorbent tools. They should therefore be soaked in water and disposed of in a hermetically sealed container. Observe local waste disposal regulations.



Step 4: Clean tools

Clean all the required tools thoroughly with water.



The safety advice and instructions for use on the containers, the product information and the safety data sheet must be observed. Please also observe the cleaning and maintenance recommendations of the manufacturers as well as the instruction manual of the machines and equipment used.