



Application method

Wax removal

For the removal of solvent-based wax, tar, oil, bitumen and scuff and heel marks. Only use on solvent-resistant base materials such as wood, cork and clay tiles (cotto).



Step 1: Ensure you have the machines and devices to hand

Rotary floor machine with pad holder and solvent-resistant pad or brush, mop holder and covers, adhesive tape, neoprene squeegee, cleaning rag, cotton waste, paper towel

Personal protective equipment



Step 2: Protect nearby floor areas

Cover nearby floor areas, furniture, equipment, cable ducts etc. with foil and affix with water-resistant, residue-free, removable adhesive tape.



Step 3: Remove coarse dirt

Damp wipe or use a vacuum cleaner to remove coarse dirt.



The safety advice and instructions for use on the containers, the product information and the safety data sheet must be observed. Please also observe the cleaning and maintenance recommendations of the manufacturers as well as the instruction manual of the machines and equipment used.



Application method

Wax removal



Step 4: Apply Kiehl-Wax-Ex

Observe the product information!

Distribute Kiehl-Wax-Ex over approx. 5 m² floor area and scrub with a rotary floor machine and pad or brush. Use a hand pad or spatula to work on the edges. Then work on the next 5 m².



Step 5: Absorb the loosened wax

Collect the loosened wax and dirt with a squeegee and then absorb with a cotton waste or other absorbent material. Do not use a wet vacuum cleaner! Risk of explosion! Dispose of soaked cloths in line with local waste disposal regulations.

