

Kiehl-Holzöl

Impregnation oil for basic treatment

Features

Based on natural raw materials. Enhances the natural colour of the wood. Does not contain perfumes or solvents, is oxidatively drying, and diffusion-open. Easy to handle, good penetration properties, impregnating, high-filling capacity. Tread and wipe-proof after 2 to 3 days hardening time. Once the floor has completely hardened, you can treat it with Kiehl-Legnodur for further protection.

Ingredients

Natural oils and resins, drying agents.

Application

Suitable for the maintenance of all European types of wood. With untreated exotic woods, please always test a small inconspicuous spot before use. For the basic treatment of wooden surfaces, such as parquet, planks, paving, industrial parquet, UV-oiled parquet, stairs, OSB boards, glued laminated timber, etc. Not suitable for sealed, coated, or waxed wooden surfaces.

Directions

It is imperative that floors are clean, dry and free from polish, wax, silicone, dust, etc. before Kiehl-Holzöl is applied. The temperature of the floor needs to be between 10°C and 25°C. Rooms have to be well ventilated while working and during the drying time; do not smoke. Shake well before use! During the hardening time (approx. 2 to 3 days) the surface is not resistant and must not be wiped.

Should only be used on untreated, clean and dust-free professionally-sanded wooden floors (or repaired with wood cement and fine-sanded - grain size 100-120).

How to use it?

Distribute approx. 800 ml Kiehl-Holzöl on about 10 square metres in a thin layer using a waxer, flat mop or Kiehl oil roller. Let the oil soak into the wood for approx. 30 minutes. If dry spots occur during this time, use the working tool to moisten the area with the Kiehl-Holzöl still remaining on the surface. If necessary, add Kiehl-Holzöl.

After 30 minutes, thoroughly remove excess Kiehl-Holzöl with a neoprene squeegee (solvent-resistant) and absorb it with cotton waste, a small shovel or something similar. Before hardening, the very thin oil film still remaining on the surface has to be completely removed. Use rotary floor machine equipped with Finish-Pad. Turn the pad and replace it with a new one in time to ensure that the oil film is entirely removed so that the surface can dry evenly. Average consumption for 10 square metres = 1 pad (both sides). Observe warning label!

After 12 hours of drying time, we recommend polishing the floor with a rotary floor machine and Finish-Pad again to remove Kiehl-Holzöl which has leaked from the joints and to optimise the appearance of the treated wooden surface.

Use Kiehl-Wax-Ex to clean working tools. Open containers have to be used up rapidly.

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product.

Warning label: Oil-saturated cloths or pads etc. can spontaneously combust.

They should therefore be soaked in water and disposed in a hermetically sealed container. Observe local disposal regulations.



Maintenance and cleaning of wood / parquet

Coverage per square metre

Basic treatment: 80-120 ml, depending on the absorbency of the wood.

Xi, Irritant in concentrated form;

R 43 May cause sensitization by skin contact. S 24 Avoid contact with skin.

Contains tung oil.

No consumer product according to 1999/44/EC Art. 1! For professional use only!

Packaging

Carton of 2x5 litre containers

Art. No. j 22 03 05

Protect from frost!

