

Kiehl-Pflegeöl

Impregnation oil for re-oiling

Features

Solvent-based wood protection made from natural raw materials. Brightens the colour of faded oiled wooden floors. Does not contain perfumes or pigments, is oxidatively drying, and diffusion-open. Easy to handle, good penetration properties, fast hardening (about 24 hours).

Ingredients

Natural oils and resins, drying agents, solvents.

Application

For re-oiling wooden surfaces which have been impregnated with oil.
Not suitable for sealed, coated, waxed or wooden surfaces with a film-building oil.

Directions

It is imperative that floors are clean, dry and free from polish, wax, silicone, dust, etc. before Kiehl-Pflegeöl is applied. The temperature of the floor needs to be between 10°C and 25°C. Rooms have to be well ventilated while working and during the drying time; do not smoke. Shake well before use! During the hardening time (approx. 24 hours) the surface is not resistant and must not be wiped.

Wood surfaces subject to hard wear first have to be dry-cleaned mechanically (rotary floor machine, suction ring, vacuum unit, Kiehl-Legno-Pad). Move machine in spirals until the surface dirt has been dissolved and the floor is thoroughly clean, presenting an even appearance. Finally, remove any remaining sanding dust with damp cloths.

How to use it? Apply approx. 250 ml on the floor and immediately distribute on about 10 square metres in a thin layer and overlapping paths, using a waxer or a flat mop. Let the oil soak into the wood for approx. 30 minutes.

If dry spots occur during this time, use the working tool to moisten the area with the Kiehl-Pflegeöl still remaining on the surface. If necessary, add Kiehl-Pflegeöl.

After 30 minutes, thoroughly remove excess Kiehl-Pflegeöl with a neoprene squeegee (solvent-resistant) and absorb it with cotton waste, a small shovel or something similar. Before hardening, the very thin oil film still remaining on the surface has to be completely removed. Use rotary floor machine equipped with Finish-Pad. Turn the pad and replace it with a new one in time to ensure that the oil film is entirely removed so that the surface can dry evenly. Observe warning label!

After 6 hours of drying time, we recommend polishing the floor with a rotary floor machine and Finish-Pad again to remove oil which has leaked from the joints and to optimise the appearance of the treated wooden surface.

Use Kiehl-Wax-Ex to clean working tools.
Open containers have to be used up rapidly.

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product.

Warning label: Oil-saturated cloths or pads etc. can spontaneously combust. They should therefore be soaked in water and disposed in a hermetically sealed container. Observe local disposal regulations.



Maintenance and cleaning of wood / parquet

Coverage per square metre

Re-oiling: 20-30 ml, depending on the absorbency of the wood.

Xn, Harmful in concentrated form;
R 43 May cause sensitization by skin contact. R 65 Harmful: may cause lung damage if swallowed. R 66 Repeated exposure may cause skin dryness or cracking. R 67 Vapours may cause drowsiness and dizziness. S 24 Avoid contact with skin. S 51 Use only in well ventilated areas. S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
Contains hydrocarbons.

No consumer product according to 1999/44/EC Art. 1! For professional use only!

Packaging

Carton of 2 x 5 litre container

Art. No. j 22 04 05

Protect from frost!

